

 This Mark is a trademark or registered trademark of NRC Forum, Inc. in the United States and in other countries.

 This product is conformant to High Fidelity Audio standard defined by Japan Audio Society "The High-Fidelity Audio logo is under license from Japan Audio Society."

The power delivered by the charger must be between min (25 Watts) required by the radio equipment, and max (35 Watts) in order to achieve the maximum charging time.

USB PD fast charging (Power Delivery) is supported.

USB PD fast charging (Power Delivery) is supported (5V, 3.3V, 5V, 9V, 12V, 15V, 20V, 28V, 33V, 45V, 50V, 55V, 60V, 65V, 70V, 75V, 80V, 85V, 90V, 95V, 100V, 105V, 110V, 115V, 120V, 125V, 130V, 135V, 140V, 145V, 150V, 155V, 160V, 165V, 170V, 175V, 180V, 185V, 190V, 195V, 200V, 205V, 210V, 215V, 220V, 225V, 230V, 235V, 240V, 245V, 250V, 255V, 260V, 265V, 270V, 275V, 280V, 285V, 290V, 295V, 300V, 305V, 310V, 315V, 320V, 325V, 330V, 335V, 340V, 345V, 350V, 355V, 360V, 365V, 370V, 375V, 380V, 385V, 390V, 395V, 400V, 405V, 410V, 415V, 420V, 425V, 430V, 435V, 440V, 445V, 450V, 455V, 460V, 465V, 470V, 475V, 480V, 485V, 490V, 495V, 500V, 505V, 510V, 515V, 520V, 525V, 530V, 535V, 540V, 545V, 550V, 555V, 560V, 565V, 570V, 575V, 580V, 585V, 590V, 595V, 600V, 605V, 610V, 615V, 620V, 625V, 630V, 635V, 640V, 645V, 650V, 655V, 660V, 665V, 670V, 675V, 680V, 685V, 690V, 695V, 700V, 705V, 710V, 715V, 720V, 725V, 730V, 735V, 740V, 745V, 750V, 755V, 760V, 765V, 770V, 775V, 780V, 785V, 790V, 795V, 800V, 805V, 810V, 815V, 820V, 825V, 830V, 835V, 840V, 845V, 850V, 855V, 860V, 865V, 870V, 875V, 880V, 885V, 890V, 895V, 900V, 905V, 910V, 915V, 920V, 925V, 930V, 935V, 940V, 945V, 950V, 955V, 960V, 965V, 970V, 975V, 980V, 985V, 990V, 995V, 1000V, 1005V, 1010V, 1015V, 1020V, 1025V, 1030V, 1035V, 1040V, 1045V, 1050V, 1055V, 1060V, 1065V, 1070V, 1075V, 1080V, 1085V, 1090V, 1095V, 1100V, 1105V, 1110V, 1115V, 1120V, 1125V, 1130V, 1135V, 1140V, 1145V, 1150V, 1155V, 1160V, 1165V, 1170V, 1175V, 1180V, 1185V, 1190V, 1195V, 1200V, 1205V, 1210V, 1215V, 1220V, 1225V, 1230V, 1235V, 1240V, 1245V, 1250V, 1255V, 1260V, 1265V, 1270V, 1275V, 1280V, 1285V, 1290V, 1295V, 1300V, 1305V, 1310V, 1315V, 1320V, 1325V, 1330V, 1335V, 1340V, 1345V, 1350V, 1355V, 1360V, 1365V, 1370V, 1375V, 1380V, 1385V, 1390V, 1395V, 1400V, 1405V, 1410V, 1415V, 1420V, 1425V, 1430V, 1435V, 1440V, 1445V, 1450V, 1455V, 1460V, 1465V, 1470V, 1475V, 1480V, 1485V, 1490V, 1495V, 1500V, 1505V, 1510V, 1515V, 1520V, 1525V, 1530V, 1535V, 1540V, 1545V, 1550V, 1555V, 1560V, 1565V, 1570V, 1575V, 1580V, 1585V, 1590V, 1595V, 1600V, 1605V, 1610V, 1615V, 1620V, 1625V, 1630V, 1635V, 1640V, 1645V, 1650V, 1655V, 1660V, 1665V, 1670V, 1675V, 1680V, 1685V, 1690V, 1695V, 1700V, 1705V, 1710V, 1715V, 1720V, 1725V, 1730V, 1735V, 1740V, 1745V, 1750V, 1755V, 1760V, 1765V, 1770V, 1775V, 1780V, 1785V, 1790V, 1795V, 1800V, 1805V, 1810V, 1815V, 1820V, 1825V, 1830V, 1835V, 1840V, 1845V, 1850V, 1855V, 1860V, 1865V, 1870V, 1875V, 1880V, 1885V, 1890V, 1895V, 1900V, 1905V, 1910V, 1915V, 1920V, 1925V, 1930V, 1935V, 1940V, 1945V, 1950V, 1955V, 1960V, 1965V, 1970V, 1975V, 1980V, 1985V, 1990V, 1995V, 2000V, 2005V, 2010V, 2015V, 2020V, 2025V, 2030V, 2035V, 2040V, 2045V, 2050V, 2055V, 2060V, 2065V, 2070V, 2075V, 2080V, 2085V, 2090V, 2095V, 2100V, 2105V, 2110V, 2115V, 2120V, 2125V, 2130V, 2135V, 2140V, 2145V, 2150V, 2155V, 2160V, 2165V, 2170V, 2175V, 2180V, 2185V, 2190V, 2195V, 2200V, 2205V, 2210V, 2215V, 2220V, 2225V, 2230V, 2235V, 2240V, 2245V, 2250V, 2255V, 2260V, 2265V, 2270V, 2275V, 2280V, 2285V, 2290V, 2295V, 2300V, 2305V, 2310V, 2315V, 2320V, 2325V, 2330V, 2335V, 2340V, 2345V, 2350V, 2355V, 2360V, 2365V, 2370V, 2375V, 2380V, 2385V, 2390V, 2395V, 2400V, 2405V, 2410V, 2415V, 2420V, 2425V, 2430V, 2435V, 2440V, 2445V, 2450V, 2455V, 2460V, 2465V, 2470V, 2475V, 2480V, 2485V, 2490V, 2495V, 2500V, 2505V, 2510V, 2515V, 2520V, 2525V, 2530V, 2535V, 2540V, 2545V, 2550V, 2555V, 2560V, 2565V, 2570V, 2575V, 2580V, 2585V, 2590V, 2595V, 2600V, 2605V, 2610V, 2615V, 2620V, 2625V, 2630V, 2635V, 2640V, 2645V, 2650V, 2655V, 2660V, 2665V, 2670V, 2675V, 2680V, 2685V, 2690V, 2695V, 2700V, 2705V, 2710V, 2715V, 2720V, 2725V, 2730V, 2735V, 2740V, 2745V, 2750V, 2755V, 2760V, 2765V, 2770V, 2775V, 2780V, 2785V, 2790V, 2795V, 2800V, 2805V, 2810V, 2815V, 2820V, 2825V, 2830V, 2835V, 2840V, 2845V, 2850V, 2855V, 2860V, 2865V, 2870V, 2875V, 2880V, 2885V, 2890V, 2895V, 2900V, 2905V, 2910V, 2915V, 2920V, 2925V, 2930V, 2935V, 2940V, 2945V, 2950V, 295

Spécifications		Spécifications de l'ardoire défilée	
Produit	RAM001	Boite	Fidélité
Présentation et couleur de l'emballage	17 (220 mm, 8,67")	Boite	Boite 1000 g (2,205 lb)
Chimiosensibilité	153 (57,737 364,7 98 mm)	MOYENNE	MOYENNE
Résistance	1000000 (10 000 000) 1000000 (10 000 000) 1000000 (10 000 000)	Boite 1000 g (2,205 lb)	Boite 1000 g (2,205 lb)
Arrière	1000000 (10 000 000) 1000000 (10 000 000) 1000000 (10 000 000)	Boite 1000 g (2,205 lb)	Boite 1000 g (2,205 lb)
Température et humidité	1000000 (10 000 000) 1000000 (10 000 000) 1000000 (10 000 000)	Boite 1000 g (2,205 lb)	Boite 1000 g (2,205 lb)
Volume de l'ardoire	1000000 (10 000 000) 1000000 (10 000 000) 1000000 (10 000 000)	Boite 1000 g (2,205 lb)	Boite 1000 g (2,205 lb)