SPARCO

IMPULSE MILTON 07545RBtgBM

sparco Teamwork

P.P.E. CAT.2: EN ISO 20345:2022	SIZE: 36/48 (3½ /13)	MONDOPOINT: 11	MADE IN: P.R.C

PICTURES

MILTON ESD S1PS SR FO HRO
07545RBtgBM

METAL FREE | ESD | HRO

DESCRIPTION

Running style safety footwear in special ORACLE RED BULL RACING LIVERY compliant with the newEN ISO 20345:2022. Seamless upper in ultra-breathable 3D fabric, anti-abrasion TPU reinforcements and 3D HF details. EVA midsole and "FO+HRO" rubber tread. Lightweight and sporty, to enhance the dynamicity of those who wear them.

FEATURES

UPPER:
seamless breathable micro-perforated 3D fabric, anti-abrasion TPU reinforcements and 3D HF details.

LINING:
breathable micro-perforated 3D fabric.

REMOVABLE INSOLE:
antistatic PU low density with ergonomic thermoforming.

ANTI-PERFORATION INSOLE:
made from zero-perforation ultralight textile fiber (PS - nail Ø 3.0 mm).

TOE CAP:
non magnetic fiberglass, insulating, resistant to 200J.

ANTI-SLIP ANTI-STATIC SOLE:
super-comfortable EVA midsole, high energy absorption and FO+HRO nitrile rubber tread.

PLUS:
Second pair of **RED** laces included.
Anti-slipping microfiber insert in the heel area.
Metal free.

DETAILS

LOGOS and **DECORATIONS** microinjected.
3D High Frequency details on **TPU** reinforcements.

SEAMLESS construction.

OUTSOLE

Segmented profiles to facilitate bending as well as the flow of liquids.

Sculpted lugs for greater slip resistance.

Segmented profiles for self-cleaning action and outflow of liquids.

A- Coefficient of friction forward heel	0,33 (≥ 0,31)
B- Coefficient of friction backward forepart	0,36 (≥ 0,36)

ANTI-SLIP ANTI-STATIC SOLE made of super comfortable EVA midsole, high energy absorption and **SR + FO + HRO** nitrile rubber tread.

REMOVABLE INSOLE

REMOVABLE INSOLE
antistatic PU low density with ergonomic thermoforming.

SPARCO

IMPULSE MILTON 07545RBtgBM

SPARCO Teamwork

| P.P.E. CAT.2: EN ISO 20345:2022	SIZE: 36/48 (3½ /13)	MONDOPOINT: 11	MADE IN: P.R.C

USER MANUAL

MULTILANGUAGE USER MANUAL: (IT, EN, ES, DE, FR, BG, CS, ET, GR, HR, HU, LT, LV, NL, PL, PT, RO, SK, SL, SV)
Dimension: 120 x 165 mm

LABELLING

TEAMWORK TAPE printed on the tongue (15x60 mm) . **ESD** mark printed on lace hooks. **ORACLE RED BULL RACING** microinjection.

COMPOSITION LABEL
applied to the right shoe
Size 28 x 28mm

Sparco S.p.A. - via Leini 524 - 10088 Volpiano (TO) - Italy
www.sparcoteamwork.com
IMPULSE ESD S1PS SR HRO
07545 RB-BM - **MILTON**
EN ISO 20345:2022 S1PS SR FO HRO
lotto1234 MM/YYYY   **MADE IN P.R.C.**

"CE" LABEL
inside the tongue
Size 50 x 15mm

EURO   UK
44   9½

SIZE LABEL
sewn between upper and tongue
Size 17 x 14mm

PACKAGING

Cardboard SPARCO RED BULL SHOE-BOX.
Protective inner tissue paper. Size: 343x188x123 mm
Recycling info at the bottom (PAP20 - valid for Italy only)
HANG TAG RED BULL 130X60 mm

SHOE-BOX LABEL reporting product's features, certification, batch number, code, QR-code and Barcode.
Size. 105x60 mm

IMPULSE MILTON 07545RBtgBM

P.P.E. CAT.2: EN ISO 20345:2022	SIZE: 36/48 (3½ /13)	MONDOPOINT: 11	MADE IN: P.R.C

TECHNICAL FEATURES