

PATH TO THE FUTURE

Der MSI MAG 325CQRF QD E2 Esports-Gaming-Monitor bietet ein 32-Zoll-WQHD-Display, 180 Hz Bildwiederholrate und 0,5 ms Reaktionszeit. Für maximale Performance und den entscheidenden Vorteil in jedem Gaming-Duell.



SELLING POINTS

- Rapid-VA-Panel - Bietet eine Reaktionszeit von 0,5 ms (GtG, Min.), optimiert Bildschirmfarben und Helligkeit.
- 180 Hz Bildwiederholrate - Reagiere schneller mit flüssigeren Bildern.
- 0,5 ms (GtG, Min.) Reaktionszeit - Vermeidet Bildschirmrisse und ungleichmäßige Bildraten.
- Verstellbarer Standfuß - Ändere die Position des Monitors mühelos für maximale Ergonomie.
- MSI Gaming Intelligence™ bietet eine Reihe intelligenter Gaming-Funktionen auf Basis von KI-Technologien für ein verbessertes Spielerlebnis.
- Aktualisiere die Firmware über die USB-Verbindung, die einfach zu bedienen ist und dich stets auf dem neuesten Stand hält.
- AI Vision - Die neue AI Vision-Technologie kann nicht nur Details in dunklen Bereichen aufdecken, sondern auch die allgemeine Helligkeit verbessern und Farben satter darstellen.



1. 5-Wege Joystick Navigation
2. Stromanschluss
3. Kopfhöreranschluss
4. DisplayPort 1.4a
5. 2 x HDMI™ 2.0b(WQHD@144Hz)
6. USB Typ-C (PD 65W)
7. USB 2.0 Typ-B
8. 2 x USB 2.0 Typ-A
9. Kensington Lock

SPECIFICATION

| | | | |
|---------------------------------------|---|------------------------------------|----------------------------|
| Model | SKU Number | 9S6-3DC14H-060 | |
| | Entity MKT Name | MAG 325CQRFDE QD E2 | |
| | Part No | 9S6-3DC14H-060 | |
| | Color | ID1/Black-Black | |
| Display | Screen Size | 31.5" (80.01 cm) | |
| | Active Display Area (mm) | 697.344x392.256 | |
| | Curvature | Curve 1000R | |
| | Panel Type | Rapid VA | |
| | Resolution | 2560x1440 (WQHD) | |
| | Pixel pitch (mm) | 0.2724(H)x0.2724(V) | |
| | Aspect Ratio | 16:9 | |
| | Dynamic Refresh Rate technology | Adaptive-Sync | |
| | Dynamic Refresh Rate Activated Range | 48~180Hz | |
| | HDR (High dynamic range) | HDR Ready | |
| | SDR Brightness (nits) | 300 | |
| | Contrast Ratio | 3500:1 | |
| | DCR (Dynamic Contrast Ratio) | 100000000:1 | |
| | Signal Frequency | 90.90~248.25 KHz(H) / 48~180 Hz(V) | |
| | Refresh Rate | 180Hz | |
| | Response Time (MPRT) | 1ms(MPRT) | |
| | Response Time (GTG) | 0.5ms | |
| | View Angles | 178°(H)/178°(V) | |
| | NTSC (CIE1976 area percentage/overlap) | 121%/92% | |
| | NTSC (CIE1931 area percentage/overlap) | 104%/92% | |
| | sRGB (CIE1976 area percentage/overlap) | 141%/99% | |
| | sRGB (CIE1931 area percentage/overlap) | 146%/99% | |
| | Adobe RGB (CIE1976 area percentage/overlap) | 119%/96% | |
| | Adobe RGB (CIE1931 area percentage/overlap) | 108%/96% | |
| | DCI-P3 (CIE1976 area percentage/overlap) | 111%/97% | |
| | DCI-P3 (CIE1931 area percentage/overlap) | 108%/94% | |
| | Rec.709 (CIE1976 area percentage/overlap) | 141%/99% | |
| | Rec.709 (CIE1931 area percentage/overlap) | 146%/99% | |
| | Rec.2020 (CIE1976 area percentage/overlap) | 80%/80% | |
| | Rec.2020 (CIE1931 area percentage/overlap) | 77%/77% | |
| | Surface Treatment | Anti-glare | |
| Display Colors | 1.07B | | |
| Color bit | 10 bits (8 bits + FRC) | | |
| Schnittstellen | USB Type C (DisplayPort Alternate) | 1 | |
| | Headphone-out | 1 | |
| | USB 2.0 Type A | 2 | |
| | USB 2.0 Type B | 1 | |
| | Card reader | N/A | |
| | Lock type | Kensington Lock | |
| | HDMI | 2 | |
| | HDMI version | 2.0b | |
| | HDMI HDCP version | 2.3 | |
| | DisplayPort | 1 | |
| | DisplayPort version | 1.4a | |
| | DisplayPort HDCP version | 2.3 | |
| | Garantie | Warranty | 36 Monate Pick-Up & Return |
| | Power | Power Type | External Adaptor 19V 7.89A |
| Power Input | | 100~240V, 50/60Hz | |
| On-mode Power Consumption (KWh/1000h) | | 32 | |
| Annual Energy Consumption (KWh) | | 53 | |
| Standby-mode Power Consumption (W) | | 0.5 | |
| Off-mode Power Consumption (W) | | 0.3 | |
| Energy Efficiency Rating | | F | |
| Power Cord Type | C5 | | |

| | | |
|------------------------------------|--|--------------------------|
| Zubehör | DisplayPort Cable | 1 |
| | HDMI Cable | 0 |
| | DVI Cable | 0 |
| | USB Type A to Type B Cable | 1 |
| | USB Type C to Type A Cable | 0 |
| | USB Type C to Type C Cable | 0 |
| | Thunderbolt Cable | 0 |
| | VGA Cable | 0 |
| | 3.5mm audio Cable | 0 |
| | 3.5mm combo audio Cable | 0 |
| | 3.5mm Mic Cable | 0 |
| | Power Cord | 1 |
| | AC Adaptor | 1 |
| | Quick Guide | 1 |
| | Warranty Card | 0 |
| | Mouse Bungee Unit | 0 |
| Design | Adjustment (Tilt) | -5° ~ 15° |
| | Adjustment (Swivel) | -30° ~ 30° |
| | Adjustment (Height) | 0 ~ 100 mm |
| | VESA Mounting | 100x100mm |
| Abmessungen & Gewicht (Product) | Product Dimension with Stand (WxDxH) (mm) | 704.62 x 280.98 x 467.02 |
| | Product Dimension without Stand (WxDxH) (mm) | 704.62 x 143.45 x 422.35 |
| | Stand Dimension (WxDxH) (mm) | 549.89 x 278.34 x 416.01 |
| | Weight (Net kg) | 7.55 |
| | Weight Without Stand (kg) | 5.8 |
| Abmessungen & Gewicht (Verpackung) | Inside Carton Dimension (WxDxH) (cm) | N/A |
| | Outer Carton Dimension (WxDxH) (cm) | N/A |
| | Weight (Gross kg) | 10.9 |
| Barcode Info | EAN | 4711377213653 |