

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Shenzhen Ketuo Hengtong Electronics Co.,Ltd.

Supplier's address: AOCE INFORMATION TECHNOLOGY S.R.L, STR. NICOLAE BALCESCU NR.12 CAMERA C2 MODULUL B58 ET.1 Bacau ROMANIA 600051

Model identifier: CFL102

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Connecting leads		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------


General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	28	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	3 080 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000 or 6 500
On-mode power (P_{on}), expressed in W	28,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, light-	Height	205	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	490	
	Depth	490	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,368 0,371
Parameters for LED and OLED light sources:			
R9 colour rendering index value	24	Survival factor	1,00
the lumen maintenance factor	0,97		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,95	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1

(a): not applicable;

(b): not applicable;



Model placed on the Union market from 29/01/2026.



EPREL registration number: 2615281

<https://eprel.ec.europa.eu/qr/2615281>

Supplier: AOCE INFORMATION TECHNOLOGY S.R.L (Authorised representative) **Website:**

Customer care service:

Name: AOCE INFORMATION TECHNOLOGY S.R.L

Website:

Email: aoce-service@outlook.com

Phone: +40-317800140

Address:

STR. NICOLAE BALCESCU NR.12 CAMERA C2 MODULUL B58 ET.1 Bacau ROMANIA 600051