Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Honeywell

Supplier's address: MEGA LAGES SAS, Bureau 450, 37 passage du Ponceau, Paris, France, Paris, FR

Model identifier: HWT-H9

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No


Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	F
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	1 400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 500
On-mode power (P_{on}), expressed in W	17,9	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control — Height	600	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
Outer dimensions without separate control gear, lighting control — Width	373		
Outer dimensions without separate control gear, lighting control — Depth	480		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power[(a)]		-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,364 0,360
Parameters for directional light sources:				
Peak luminous intensity (cd)		505	Beam angle in degrees, or the range of beam angles that can be set	110
Parameters for LED and OLED light sources:				
R9 colour rendering index value		62	Survival factor	0,90
the lumen maintenance factor		0,93		

[(a)] '-' : not applicable;

[(b)] '-' : not applicable;


1.0
0.5
380
460
540
620
700
780

EPREL registration number: 2727883 Model placed on the Union market from 15/05/2026.	https://eprel.ec.europa.eu/qr/2727883

Supplier: Mega Lages SAS (Authorised representative) **Website:**

Customer care service:

Name: MEGA LAGES SAS **Website:**

Email: admin@mega-lages.com **Phone:** +33-170613157

Address:
Bureau 450, 37 passage du Ponceau, Paris, France
Paris
France