

Circular Saw LXT®

DSS611

18 V • 3 700 min- • 165 mm

18V LXT® Cordless saw that cuts at high rotational speed of 3,700 RPM . Saw's grip provides more control and comfort. Easy to adjust cutting depth with safety cover with calibration line. Aluminum base provides high quality and toughness for better work results. Bevel cuts from 0° to 45° for the most common cutting applications



Technical specifications

| | |
|--|------------------------|
| Nominal Battery Voltage | 18 V |
| Voltage LXT | ✓ |
| Max. Cutting Depth at 90° | 57 mm |
| Max. Cutting Depth at 45° | 40 mm |
| Max. Cutting Depth at 50° | 36 mm |
| Max. Bevel Range (Left) | 0 / 45 ° |
| No load speed | 3700 min ⁻¹ |
| Tool weight with battery (EPTA) | 2,9 - 3,2 kg |
| Product Dimensions (L x W x H): | 347 x 202 x 228 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Max Output Power | 360 W |
| Capacity 45° | 40 mm |
| Blade Diameter | 165 mm |
| Bore Size (Arbor Diameter) | 20 / 30 mm |
| Product net weight | 2,4 kg |

User benefits

- Smooth cutting at high rotational speed of 3,700 RPM
- Easy to grip, ergonomically designed handle with soft grip provides a sure and comfortable grip
- Safety cover with calibration line for adjusting cutting depth
- Bevel cuts 0° - 45°
- Large bevel lock lever; Easy to operate even if the machine is placed close to the wall, because you do not need to reach for the rear of the machine to turn the lever
- Externally accessible brushes for easy serviceability

Link to product - www.makitauk.com



Related products

Optional AC

141353-9
Plastic Carrying Case



164095-8
Parallel Guide



783203-8
Hex Wrench 5 Mm



821551-8
Makpac case (3)



837628-9
MakPac (3) Inlay



Other

User manual