

SHORT THROW SERIES IN116BBST



WXGA - 3600 * - 16:10 Aspect Ratio

The IN116BBST short-throw projector does more with ultra-long lamp life, high brightness, and amazing connectivity. Beam more perfect images and engage your audience with 2 HDMI inputs, VGA, video, and audio capability. Plus, the compact design and lightweight makes it as easy to move around as it is to install.

Features

Low Latency Gaming Mode

Improved communication time from the input source to your projector allows for an enhanced gaming experience.

USB-A Power for Devices

Power your external devices like Amazon Firestick or Roku with the convenient USB-A input right on the projector.

Industry-leading Lamp Life

The Genesis Series features up to an unprecedented 15,000 hours of lamp life when used in Dynamic Mode. With no filters to replace, these projectors are an unbeatable value.

High Brightness

Get better, brighter images on any surface, in any light. The Genesis Series has up to 3800 lumens.

Advanced Digital Image Correction

With the new digital edge masking and image shift features – we make getting those final image adjustments perfect.

Zoom

The zoom ratio adds flexibility for installations using pre-existing mounts. Adjust the zoom to create the perfect image in the same space.

BILD

Projektionstechnologie	Texas Instruments DLP®
Bildgröße	0.55" DMD
Bildaufösung	WXGA
Pixel	1280 x 800
Bildformat	16:10
Kontrasverhältnis	30000:1
Helligkeit (Lumen)	3600

Lichtquelle	UHP Lamp
Lebenszeit der Lichtquelle (in Stunden)	15000
Maximal unterstützte Auflösung	1920 x 1200
Horizontale Synchronisation	31.469 ~ 97.551
Vertikale Synchronisation	56 ~ 85
Gleichmässige Ausleuchtung (%)	80

OPTIK

Linse	1.1x
Anpassung des Zooms	Fixed Lens
Optische Linsen	-
Bildversatz (%)	112.4
Brennweite (mm)	7.15
F-Stop	2.8
Vertikale Linsenversatz	-
Horizontale Linsenversatz (%)	-
Keystone Korrektur	Manual
Vertikale Keystone Korrektur	±20
Horizontale Keystone Korrektur	-
Projektionsfaktor	0.52:1
Projektionsdistanz (Meter / Fuß)	0.4 ~ 3.3 / 1.3 ~ 11
Optischer Zoom	1:1
Digitaler Zoom (Verkleinerung / Vergrößerung)	0.8x ~ 2.0x
Fokuskorrektur	Manual

VERBINDUNGEN

Inputs	
Mini D-sub 15-pin (VGA)	✓
Composite Video	-
S-Video	✓
HDMI™ 1.4	✓ ✓
HDMI™ 2.0	-
USB-B 2.0	-
RJ45 - LAN 10/100/1000	-
3.5 mm Stereo Mini Jack	✓
3.5 mm Stereo Mini Jack with Microphone	-
Outputs	
Mini D-sub 15-pin (VGA)	✓
3.5 mm Stereo Mini Jack	✓
Powered USB-A for Wireless Dongle	✓
3D Synchronisation	-
Other	
RS232	✓
RJ45 HDBaseT	-
All Major 3D Formats	✓
USB-B 2.0 for Service	-

USB-A for Service	✓
Micro USB for Service	-
Dokumentbetrachter	-
Videoplayer	-
Bildwiedergabe	-
Musikwiedergabe	-
12v Screen Trigger	-

ENERGIE

Stromversorgung	100-240 V AC; 50 ~ 60 Hz
maximale Stromaufnahme (Watt)	267
Power Consumption Min. (W)	210
Stromaufnahme im Netzwerk Ruhezustand (Watt)	-
Stromaufnahme im Ruhezustand (Watt)	<0.5

ALLGEMEIN

Abmessungen (Breite x Höhe x Tiefe) (mm/Zoll)	236 x 313 x 107 / 9 x 12 x 4
Gewicht (Kilogramm/Pfund)	2.6 / 5.7
Lautstärke des Lüfters [dB (A)]	30
Audio (W)	10
Operating Temperature (Celsius/Fahrenheit)	5 ~ 40 / 41 ~ 104
Betriebsfeuchtigkeit [%]	10 ~ 85
Betriebshöhenlage (Meter / Fuß)	3048 / 10000
Lagertemperatur [°C/F]	-10 ~ 60 / 14 ~ 140
Lagerfeuchtigkeit [%]	10 ~ 85
Sicherheit	Kensington Security Slot™ x1, PIN Code Lock & Timer
Lieferumfang	Power cord, VGA cable, Safety instructions, User documentation, Remote control without batteries
Sicherheit und Regulationen	CB, CE, EAC, cTUVus, CCC, FCC, UKCA, NOM, PSB, BIS
Umweltbestimmungen	WEEE, EU RoHS, China RoHS, CEL, CECF

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.