




Wall Lights | 220-240 V | 1x2G10
4896



Technische Daten	
Sammlung	linealight
Installationsposition	Wand
Installation environment	Indoor
Lampenleistung	1 x 36 W
Anschluss der Leuchte	1 x 2G10
Frequency	60 - 50 Hz
Optic	Diffused
Light emission direction	downward
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
ETL	Nein
Einschließlich Driver	Ja
Notbeleuchtung	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein Kg
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Nettogewicht	2.900 kg
Volumen	0.025 m³
Packaging size	378x175x378 mm
Number of packages	1

Oberfläche Diffusor

Material	Glass
Colour	white
Bearbeitungstyp	Silk-screening

Oberfläche Fassung

Material	Iron
Bearbeitungstyp	Coating

Wall Lights | 220-240 V | 1x2G10
4896

Single emission wall lights for indoor application. Fluorescent lamp included 36W, lamp cap 1x2G10.

; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of iron, processed by means of coating. The ingress protection degree is IP20; the total weight is of 2.900 kg. The power supply driver is included in the delivery.

The device features protection class I and can be wall lights-mounted.

Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	100 %
Lichtstrom (Lichtquelle)	2800 lm
Leuchten Lichtstrom	2800 lm
Consumption	35 W
Leuchten Lichtausbeute	81 lm/W
Farbtemperatur	3000 K
Farbwiedergabeindex	89 Ra

UGR	
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20
UGR transversal	< 19
UGR axial	< 19

