

TECHNISCHE DATEN SPECIFICATIONS		HOLZ / WOOD
Format Size		1220 x 230 mm
Stärke Thickness		4,8 mm
Vinyl- Nutzschiicht Wear layer		0,3 mm
Vergütung Coating		UV
Struktur Surface		EIR
Gefaste Kanten Bevelled edge		Ja Yes
Verbindung Connection		Uniclic
Integrierte Unterlegmatte Integrated underlay mat		Ja Yes
1 Karton Box	Stück Pieces	8
	m ²	2,245
	Kg	21,23
1 Palette Pallet	Kartons Pack	36
	m ²	80,820
	Kg netto Gross	764
	Kg brutto Gross	794
Rutschhemmstufe Antislip category	DIN 51130	R10
Rutschfestigkeitsklasse Slip resistance class	EN 14041	DS
Chemikalienbeständigkeit Chemical resistance	EN 423	Gut Good
Trittschallreduktion Sound reduction	ISO 140-8	18 dB
Verschleissverhalten Wear resistance	EN 660-2	Gr. T
Brandverhalten Flammability	BS EN 13501	B _{f1} -s1
Formaldehyd Formaldehyde		E1
Fussbodenheizung Underflooring heating	EN 649	Geeignet für elektrische Fußbodenheizung Suitable for electric underfloor heating
Nutzungsklasse Utilization class		23/31
Garantie Warranty	Wohnen Residential Mittlere gewerblich Moderate commercial	15 Jahre Years 3 Jahre Years



Produced under license of Unilin - EP nr. 0843743/U.S. patent nr. 6,006,486

