

GeForce RTX[™] 4070 VENTUS 2X E 12G OC









SPECIFICATIONS

Model Name	GeForce RTX [™] 4070 VENTUS 2X E 12G OC
Graphics Processing Unit	NVIDIA® GeForce RTX [™] 4070
Interface	PCI Express® Gen 4
Core Clocks	Extreme Performance: 2520 MHz (MSI Center) Boost: 2505 MHz
CUDA® CORES	5888 Units
Memory Speed	21 Gbps
Memory	12GB GDDR6X
Memory Bus	192-bit
Output	DisplayPort x 3 (v1.4a) HDMI [™] x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI [™] 2.1a)
HDCP Support	Y
Power consumption	200 W
Power connectors	8-pin x 1
Recommended PSU	650 W
Card Dimension (mm)	242 x 125 x 43 mm
Weight (Card / Package)	663 g / 959 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC technology	Υ
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



- ${\bf 1.\ DisplayPort}$
- 2. HDMI™

FEATURES



Dual Fai

Two fans and a huge heatsink ensure a cool and quiet experience for you.



ORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.




Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr





MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.