



# USER MANUAL



## IN THE BOX



**SPECIFICATIONS (O sight RD)**

Mode	4.3 lm	39534.5 H
Mode 3	3.5 lm	48571.4 H
Mode 2	2.6 lm	55984.6 H
Mode 1	2.4 lm	70833.3 H
OFF	2.0 lm	

**Table 2:  
Charging Cover**

Main Body	Plastic + AL6061
Dimensions	33*51*44 mm / 1.38*2.01*1.73 in
Weight	50 g / 1.76 oz
Battery Capacity	800 mAh / 3.8 V (1.1 Wh)
Input	DC 5 V / 2 A (MAX)
Output	DC 4.45 V / 0.1 A (MAX)
Time to Fully Charge the Optic	3 H

**USB-C Charging Cable**

Charge Type	USB-C
Length	0.8 m
Input	5 V / 2 A
Output	4.45 V / 0.1 A (MAX)
Time to Fully Charge the Optic	3 H

**Table 1: Optic**

Mode	430.1 H
Mode 11	134.4 H
Mode 10	94.9 H
Mode 9	52.2 H
Mode 8	151.1 H
Mode 7	111.1 H
Mode 5	55.5 H

**SPECIFICATIONS (Osight GN)**

Mode	430.1 H
Mode 11	126.9 H
Mode 10	179.1 H
Mode 9	323.9 H
Mode 8	125.8 H
Mode 7	151.5 H
Mode 5	237.3 H

**Table 3: Optic**

Mode	430.1 H
Mode 12	510.5 H
Mode 11	125.0 H
Mode 10	179.0 H
Mode 9	323.9 H
Mode 8	125.8 H
Mode 7	146.5 H
Mode 6	5.6 H
Mode 5	5.0 H
Mode 4	4.2 H
Mode 3	3.2 H
Mode 2	2.6 H
Mode 1	2.4 H
OFF	2.0 H

**Table 4: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 5: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 6: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 7: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 8: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 9: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 10: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H
Mode 7	257.0 H
Mode 6	5.0 H
Mode 5	404.6 H
Mode 4	512.0 H
Mode 3	531.0 H
Mode 2	680.0 H
Mode 1	70833.3 H
OFF	6.0 H

**Table 11: Optic**

Mode	510.5 H
Mode 12	125.0 H
Mode 11	179.0 H
Mode 10	323.9 H
Mode 9	125.8 H
Mode 8	146.5 H</td