

# Instruction Manual



# Contents

Warranty	01
What's in your box?	02
How to install the brake system and wheels	03
How to open and close your frame	04
How to attach car seat onto your frame	05
How to change bassinet/carrycot to toddler seat	06-07
How to adjust handle and seat position	08
How to correctly use the brake system	09
Fabric and stroller care	10
Warning	11

## What's in your box?



- A: BASSINET/TODDLER SEAT HOOD
- B: STROLLER HANDLE
- C: ADJUSTABLE BUTTON FOR HANDLE HEIGHT
- D: FOLDING MECHANISMS
- E: BASSINET/TODDLER SEAT HANDLE BAR
- F: SEAT ADJUSTMENT BUTTONS
- G: POCKETS
- H: BASSINET/TODDLER FRAME
- I: BASKET
- J: REAR WHEEL
- K: BRAKE SYSTEM
- L: LOCK FOR FRONT WHEEL (ANTI-SWIVEL)
- M: FRONT WHEEL

## How to install the brake system and wheels



Align brake system as indicated in photograph 1, and connect.

Once you hear the click on either side, the brake system is securely attached.



Attach rear wheels on either side of brake system, as seen in photograph 3.



You will hear a click, this indicates they are attached.



Attached the front wheels by placing the steel pin into the mechanism as shown in photograph 4.

## How to open and close your frame



1

TO OPEN:

Release safety mechanism on the right-hand side of the frame. Place both hands on either side of frame and open.



2

TO CLOSE:

Pull both mechanism while pushing the button on the right-hand side. (Refer to page 2 letter marked 'D') Please note: there is only a button on the right-hand side.



3

Once you have pulled these mechanisms, push the frame down and it will close. The safety catch will lock stroller.



4

## How to install car seat onto your frame



1

Insert car seat adapters into the car seat base on either side. You will hear a click once inserted.

This will remain in the car seat at all times and you will NOT need to remove and re-insert.



2

Align car seat to stroller frame and push down.

Once hearing a click, you are now rest assured your car seat is securely attached.



3

Car seat is attached, as seen in photograph 3.

## How to change bassinet/carrycot to toddler seat



### WHEN SHOULD WE CHANGE FROM BASSINET TO TODDLER SEAT?

Your baby is ready to move once he/she starts pulling him/herself up and wants to sit.

The toddler seat can be used from 9kg and not newborn.



You would've received the bassinet already assembled in your box as shown in photograph 1.



Remove mattress and hard board from bassinet.

Release velcro strips. There are two on the top of the frame.

It is required to pull both sides of the bassinet cover as shown in photograph 2.



Slip the material from the frame as shown in photograph 3, until you end up with the naked frame, shown in photograph 4.

## How to change bassinet/carrycot to toddler seat



You will notice two pins on either side of the frame. This indicates, the bottom half of the frame.

Slip the fabric part of the toddler seat over the top part of the frame.



Connect the velcro strips on the bottom of the frame.



Place the silver ring over the pin on both sides and connect the clip at the back of the frame as shown in photograph 8.



## How to adjust the handle and seat position

Press both buttons on either side to adjust the handle height and release.



Press both 'tilt' buttons on either side simultaneously to recline the seat.

The seat can adjust to a 45°, 60° and 75° for the perfect position ensuring your baby is comfortable.



## How to correctly use the brake system

Push break lever down to lock break.  
Push break lever up to unlock.



It is **recommended** to use the brake system in a locked position before placing your any attachment onto the frame.



Press button down marked as 'A' in photograph 2 to lock the front wheel. Once the wheel is in position it will lock automatically. To unlock, push the button upwards.

## Fabric and stroller care

### STROLLER CARE

Clean the plastic components with a damp cloth.  
DO NOT USE harsh chemicals like bleach.

In very dry climate areas, clean and lubricate the wheels, safety locks and sliding parts with light oil or silicon spray. DO NOT USE heavy oils as this will attract dust and dirt and will lead to clog and damage parts.

### FABRIC CARE

Fabric is splash resistant. In the event your stroller becomes wet, leave to dry in a shaded area and NOT in direct sunlight.

Washing instructions: Wipe clean only.

Light soiling to the fabric can be removed with a damp cloth/sponge and light detergent. DO NOT USE harsh chemicals.

## WARNING

Read this instruction manual carefully.

The maximum weight allowance for the car seat is 13kg.

To avoid the risk of suffocation, keep all plastic packaging and materials out of reach of children.

You are personally responsible for the safety of your baby at all times.

Always set the parking break on the stroller. Never leave child unattended.

Always secure your child in the safety harness at all times.

Regularly check that the safety harness is correctly fitted and that the webbing has not become frayed or damaged.