# **LUMEN KING LED**


**GROW LIGHT 400 W** 



## TECHNICAL SPECIFICATIONS

Light Source	LED
Spectrum	Full Spectrum
PPF	1080 µmol/s
Input Power	400W
Efficacy	2.7 μmol/J
Input Voltage	220-240V
Mounting Height	≥ 6 Above Canopy
Thermal Management	Passive
Dimming	PWM/Manual dimming
Beam Angle	120°
Power Factor	>90 %
Certifications	CE/UKCA/ROHS
Diodes Brand	Optimum
Drivers Brand	Optimum 400W Integrated Driver
Waterproof Rating	IP44
Operation Temperature	-25-40°C
Operation Humidity	10%-95% RH
Storage Temperature	-20° - 80°C
Storage Humidity	10%-95% RH
Warranty Period	2 years

#### **SPECTRUM**




## ITEMS INCLUDED IN THE BOX


6 x Lumen King 400W 2.7 Full Spectrum LED Light Bars
2 x 1/8" Lumen King Rope Ratchets
1 x RJ Input Network Cable
1x EU Power Cord

DIMENSIONS									
Part	LENGTH	WIDTH	HEIGHT	WEIGHT					
LUMEN KING Light fixture	750mm	750mm	54mm	5.8kg					
LUMEN KING Package Size	800mm	100mm	400mm	7.5kg					

### PRODUCT DIMENSIONS



## PPFD TESTING REPORT



HEIGHT TO TEST POINT			90 cm				HEIGHT TO TEST POINT 120 cm						
118	]56	182	184	)57	)1/		104	126	]89	140	]25	103	Ī
159	222	<u>}</u> 25€	258	220	158		126	]56	773	773	)55	124	
186	<u>}</u> 69	320	318	266	192	121.92 cm	139	]78	]98	)9{	)7 <b>5</b>	)4(	121.92 cm
190	269	322	320	269	190	12 cm	140	)7(	200	199	)7{	140	2 Cm
163	<u>}</u> 22{	262	260	219	157	TN	128	)5{	775	775	156	124	
116	<u>]</u> 56	)8(	778	150	115	24.38 cm	103	124	]39	138	)32	102	l.
		121.9	2cm		4.38 cm				121.9	2cm	-	4.38 cm	

### INFORMATION

PPF calculations compiled using our in-house integrating sphere measurements and typical spectroradiometric data for each LED fixture performance.

Wattages are typical expected values. Allow a range of 10% on flux and power consumption.

C€ ĽK RoHS

Contact Lumen-King @ info@lumen-king.com @ www.lumen-king.com/led-grow-lights @