

EAN : 542503 853124 4

SKU : SXAE00025

- Charge & maintenance functions
- Automatic management by microprocessor
- Maximum current 4 Amp
- Suitable for 6V / 12V batteries
- Up to 8 steps intelligent charging cycles
- No battery removal required
- For all types of lead-acid batteries
- Supplied with clamps and eyelets



SPECIFICATIONS

INPUT	Voltage	220 - 240 Volt AC 50 - 60Hz			
	Plug	EU	Type	Standard	
OUTPUT	Nominal Voltage	6V - 12V		Max Output	4A
	Cable length	1,5m + 0,5m clamps cable and O-rings cable			
	Terminals	Clamps and O-rings			
CAPACITY	Charge	4 - 80 Ah	Maintain	4 - 120 Ah	
	Recovery	YES			
	Compatibility	Lead Acid battery : AGM , GEL, VLRA, WET, LIQUID			
INTERFACE	LCD Display	Charging status - Error Indicator			
	MMI	3 selections: voltage - slow/fast - battery type (STD/AGM)			
IP CLASSIFICATION	IP 65				
CERTIFICATION	CE EN60335 - 2 - 29 - LVD - EMC - RoHS				

SKU	EAN code	5425038 53124 4				
	Length	165mm	Width	55mm	Height	280mm
	Gross weight	860gr	Net weight	630gr		
Carton box	EAN code	2 5425038 53124 8				
	Length	577mm	Width	198mm	Height	185mm
	Gross weight	5,20kg	Net weight	3,78kg		
	Qty of SKUs per carton box	6				
PALLET	EAN code	4 5425038 53124 2				
	Length	120cm	Width	80cm	Height	145cm
	Gross weight	322kg	Net weight	212kg		
	Carton per layer	8	Qty of layers	7	Cartons per pallet	56
	Qty SKUs per pallet	336				
	type of pallet	Plywood pallet				