

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Bettleuchte

**Supplier's address:** -

**Model identifier:** 90002501

**Type of light source:**

|   |         |                                 |      |
|---|---------|---------------------------------|------|
| Lighting technology used:                           | LED     | Non-directional or directional: | DLS  |
| Light source cap-type (or other electric interface) | SMD LED |                                 |      |
| Mains or non-mains:                                 | NMLS    | Connected light source (CLS):   | Nein |
| Colour-tuneable light source:                       | Nein    | Envelope:                       | -    |
| High luminance light source:                        | Nein    |                                 |      |
| Anti-glare shield:                                  | Ja      | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                   | Parameter  | Value  |
|--|-------------------------|--|--|
| <b>General product parameters:</b>   |                         |  |  |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 3                       | Energy efficiency class  | G  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 150 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500  |
| On-mode power ( $P_{on}$ ), expressed in W   | 4,1                     | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,50   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 83   |
| Outer dimensions without   | Height                  | 542  | Spectral power distribution in the<br>See image in last page |
|  | Width                   | 34   |  |
|  | Depth                   | 24   |  |

|   |      |  |                                      |
|---|------|--|--------------------------------------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |      |  | range 250 nm to 800 nm, at full-load |
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)                                       | -                                    |
|   |      | Chromaticity coordinates (x and y)                                 | 0,300<br>0,320                       |
| <b>Parameters for directional light sources:</b>  |      |  |                                      |
| Peak luminous intensity (cd)  | 39   | Beam angle in degrees, or the range of beam angles that can be set | 135                                  |
| <b>Parameters for LED and OLED light sources:</b>   |      |  |                                      |
| R9 colour rendering index value   | 10   | Survival factor  | 0,80                                 |
| the lumen maintenance factor  | 0,96 |  |                                      |

(a): not applicable;

(b): not applicable;