## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Searchlight Electric

Supplier's address: -

## Model identifier: 8343PB

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Integrated					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	Yes			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

		Floudet para	IIICICI S			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	13	Energy efficiency class	G		
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	600 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode p expressed in W	oower (P <sub>on</sub> ),	13,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	-		
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	82		
Outer dimensions without	Height	115	Spectral power	See image		
	Width	680	distribution in the	in last page		
	Depth	680				
				Page 1 / 1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-				
		Chromaticity coordinates (x and y)					
Parameters for LED and OLED light sources:							
R9 colour rendering index value	-	Survival factor	-				
the lumen maintenance factor	-						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-				
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-				
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-				

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;