Product Fiche compliant to commission delegated regulation (EU) No 65/2014		
Brand	KLUGMANN	
Model	KGO600.5GFX	
EEI [%] Energy Efficiency Index - Main cavity <sup>1)</sup>	71.5	
EEI [%] Energy Efficiency Index - Secondary cavity <sup>1)</sup>		
Energy Efficiency Class - Main cavity <sup>2)</sup>	A+	
Energy Efficiency Class - Secondary cavity <sup>2)</sup>		
Energy consumption in conventional mode [kWh/cycle] - Main cavity <sup>3)</sup>	1.22	
Energy consumption in conventional mode [kWh/cycle] - Secondary cavity 3)		
Energy consumption in fan-forced mode [kWh/cycle] - Main cavity <sup>3)</sup>	1.31	
Energy consumption in fan-forced mode [kWh/cycle] - Secondary cavity <sup>3)</sup>		
Energy consumption in conventional mode [MJ/cycle] - Main cavity <sup>3)</sup>	4.40	
Energy consumption in conventional mode [MJ/cycle] - Secondary cavity <sup>3)</sup>		
Energy consumption in fan-forced mode [MJ/cycle] - Main cavity <sup>3)</sup>	4.70	
Energy consumption in fan-forced mode [MJ/cycle] - Secondary cavity <sup>3)</sup>		
Number of cavities	1	
Heat source - Main cavity	GAS	
Heat Source - Secondary cavity		
Usable volume [I] - Main cavity	60	
Usable volume [I] - Secondary cavity		
1) Energy Efficiency Index calculated according to the volume and energy consumption for each cavity.		

2) From A+++ (low consumption) to D (high consumption).

3) Based on the results of standards tests that simulate the thermal properties of food. The consumption will depend on how the appliance is used.

	Symbol	Value	Unit
Nodel identification	KGO600.5GFX		
Type of oven	FAN FORCED		
Mass of the appliance	М	36.5	Kg
Number of cavities		1	
leat source per cavity (electricity or gas)		GAS	
/olume per cavity - Main cavity	V	60	
/olume per cavity - Secondary cavity	V		I
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Main cavity	EC <sub>electric cavity</sub>		kWh/cycle
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Secondary cavity	EC <sub>electric cavity</sub>		kWh/cycle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric inal energy) - Main cavity	EC <sub>electric</sub> cavity		kWh/cycle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric inal energy) - Secondary cavity	EC <sub>electric</sub> cavity		kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired		4.40	MJ/cycle kWh/cycle (a
cavity of an oven during a cycle in conventional mode per cavity (gas final	EC <sub>gas cavity</sub>		
energy) - Main cavity		1.22	KWWII/CYCIE (a
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity	EC <sub>gas cavity</sub>		MJ/cycle kWh/cycle
Energy consumption required to heat a standardised load in a gas-fired	EC <sub>gas cavity</sub>	4.70	Millovala
cavity of an oven during a cycle in fan-forced mode per cavity (gas final			MJ/cycle kWh/cycle
energy) - Main cavity		1.31	Kwii/cycle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity	EC <sub>gas cavity</sub>		MJ/cycle kWh/cycle
Energy Efficiency Index per cavity - Main cavity	EEI <sub>cavity</sub>	71.5	1
Energy Efficiency Index per cavity - Secondary cavity	EEI <sub>cavity</sub>		