Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Searchlight Electric

Supplier's address: -

Model identifier: 9909WH

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Integrated		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consu mode (kWh/1 up to the near	000 h), rounded	1	Energy efficiency class	G			
indicating if it in a sphere (3	bus flux (φuse), refers to the flux 360º), in a wide in a narrow cone	- in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	-			
On-mode expressed in W	power (P _{on}), /	-	Standby power (P _{sb}), expressed in W and rounded to the second decimal	-			
for CLS, expre	ndby power (P _{net}) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer dimensions without	Height	124	Spectral power	See image			
	Width	150	distribution in the	in last page			
	Depth	150		Page 1 / 2			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-			

(a)_{'-'} : not applicable;

(b)'-' : not applicable;