

ProArt Display PA329C

Display

Panel Size (inch) : 32
Pixels Per Inch (PPI) : 138
Aspect Ratio : 16:09
Display Viewing Area (H x V) : 708.48 x 398.52 mm
Display Surface : Non-Glare
Backlight Type : LED
Panel Type : IPS
Viewing Angle (CR \geq 10, H/V) : 178°/ 178°
Pixel Pitch : 0,185 mm
Resolution : 3840x2160
Color Space (sRGB) : 100%
Color Space (Adobe RGB) : 100%
Color Space (DCI-P3) : 98%
Color Space (Rec.2020) : 85%
Brightness (HDR, Peak) : 600 cd/m²
Brightness (Typ.) : 400cd/m²
Contrast Ratio (HDR, Max) : 1.000.000:1
Contrast Ratio (Typ.) : 1200:01:00
ASUS Smart Contrast Ratio (ASCR) : 10000000:1
Display Colors : 1073.7M (10 bit)
Response Time : 5ms(GTG)
Refresh Rate (Max) : Typ. 60Hz
HDR (High Dynamic Range) Support : HDR10
Protection Glass : Nein
Flicker-free : Ja



Video Feature

Trace Free Technology : Ja
ProArt Preset : Standard
ProArt Preset : sRGB
ProArt Preset : Adobe RGB
ProArt Preset : DCI-P3
ProArt Preset : Rec. 2020
ProArt Preset : DICOM
ProArt Preset : Rec. 709
ProArt Preset : HDR_PQ Rec2020
ProArt Preset : Benutzermodus 1
ProArt Preset : Benutzermodus 2
SPLENDID Technology : Yes
Color Temp. Selection : Yes(4 modes)
Color Adjustment : 6-Achsen-Einstellung (R,G,B,C,M,Y)
Gamma adjustment : Ja (Unterstützung von Gamma 1.8/2.0/2.2/2.4/2.6)
Color Accuracy : $\Delta E \leq 2$
ASUS ProArt Hardware Calibration : Ja
GamePlus : Nicht verfügbar
QuickFit : Yes
PIP / PBP Technology : Ja
HDCP : Yes
VRR Technology : Adaptive-Sync
Dark Boost : Ja
DisplayWidget : Nein

Low Blue Light : Yes
Multiple HDR Mode : Yes

Audio Feature

Speaker : Yes(3Wx2)

I/O Ports

USB-C x 1
DisplayPort 1.2 x 1
HDMI(v2.0) x 3
VGA Nicht verfügbar
USB Hub : 5x USB 3.2 Gen 1 Type-A
USB-C Power Delivery : 60W

Signal Frequency

Digital Signal Frequency : 30~135 KHz (H) / 24~76 Hz (V)

Power Consumption

Power Consumption : <56.84W*
Power Saving Mode : <0.5W
Power Off Mode : 0W (Hardwareschalter)
Voltage : 100-240V, 50/60Hz

Mechanical Design

Tilt : Yes (+20° ~ -5°)
Swivel : Yes (+45° ~ -45°)
Pivot : Yes (0° ~ 90° Counterclockwise)
Height Adjustment : Ja
Lighting effect : Nicht verfügbar
VESA Wall Mounting : 100 x 100 mm
Kensington Lock : Ja

Dimensions (Esti.)

Phys. Dimension with Stand (W x H x D) : 735 x 615 x 240 mm
Phys. Dimension without Stand (W x H x D) : 734.4 x 431 x 66.85 mm
Box Dimension (W x H x D) : 847 x 552 x 350 mm

Weight (Esti.)

Net Weight with Stand : 12.32 Kg
Net Weight without Stand : 8.7 Kg
Gross Weight : 16.7 Kg

Accessories (vary by regions)

Bericht zur Farbvorkalibrierung
DisplayPort Kabel
HDMI Kabel
Netzkabel
Ständer mit Schnellverschluss
Schnellstartanleitung
USB-C Kabel
USB-C zu A Kabel