


REGULATION (EU) 2019/2015**Annex V, Table 3****Product Information sheet**

Supplier' s name or trade mark:		Coen Bakker Deco B.V.	
Supplier' s address:		Smeetsweg 4a 1738 DK WAARLAND NETHERLANDS	
Model identifier:		236662	
Type of light source:		Led string light	
Lighting technology used:	LED	Led qty	30pcs
Led type:	other electric interface	Input voltage	220-240V
Power supply mode	DC adapter	Output voltage	3.4V
Dimming or not:	no	Timing or not	no
High luminance light source:	no	Connected light source (CLS):	no
Anti-glare shield:	no	Output current	588MA
Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer:	2kWh/1 000 h	Energy efficiency class:	G
Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°):	75 lumen in a wide cone (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:	[2600K]
On-mode power (P_{on}), expressed in W:	2W	Standby power (P_{sb}), expressed in W and rounded to the second decimal:	0
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal:	/	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set:	[80]

Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre):	Height:	400mm	Spectral power distribution in the range 250 nm to 800 nm, at full-load:	
	Width:	30mm		
	Depth:	40mm		
Claim of equivalent power		/	If yes, equivalent power (W)	/
			Chromaticity coordinates (x and y):	X:0.485 y:0.427
<i>Parameters for directional light sources:</i>				
Peak luminous intensity (cd):		/	Beam angle in degrees, or the range of beam angles that can be set:	/
<i>Parameters for LED and OLED light sources:</i>				
R9 colour rendering index value:		1	Survival factor:	0,90
the lumen maintenance factor:		0,9		
<i>Parameters for LED and OLED mains light sources:</i>				
displacement factor (cos ϕ 1):		0,00	Colour consistency in McAdam ellipses:	6,2
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.:		[NO]	If yes then replacement claim (W)	/
Flicker metric (Pst LM):		0,0	Stroboscopic effect metric (SVM):	0,0

