

# CORE-SERIE INL156



## INL156 - WXGA - 3500 Lumen - 16:10 Seitenverhältnis

Die Quantum Laser Core-Serie ist funktionsreich und bietet bis zu 30.000 Stunden wartungsfreien Betrieb rund um die Uhr. Konzipiert für wartungsfreien Dauerbetrieb kann die Core-Serie in praktisch jeder Ausrichtung installiert werden. Leichtgewicht mit kompakter Stellfläche in Kombination mit 360-Grad- und Hochformat-Projektion ermöglichen eine flexible und mühelose Installation.

### Merkmale

#### Lampenfrie, umweltfreundliche Lasertechnologie

Our Quantum Laser product line is reliable and environmentally friendly with solid-state laser light source technology. The complete product line is lamp, filter, mercury, and maintenance-free. The ultra-low energy usage for its class and long-standing durability and performance offers outstanding value and total cost of ownership.

#### Unparalleled Flexibility

Flexibility for almost every use model with a 1.3x optical zoom lens, front, rear, and ceiling placement and floor to ceiling projection, ceiling to floor, complete 360-degree installation across the horizontal axis, and not forgetting both landscape and portrait modes—ideal for meeting rooms, home office, classrooms, retail displays, fixed installations, bars, clubs, and restaurants and so much more.

#### Designed for maintenance-free 24/7 continuous operation

Designed for maintenance-free 24/7 continuous operation with advanced laser diode cooling and a IP6X rated dust resistant design.

#### SuperSmartProject

Our SuperSmartProject suite of power-saving, power optimisation, and utilisation features and functions combine ease of use and energy saving for your everyday use. Instant power on, signal power on, instant power off, auto power-off, 10 step illumination reduction, and Dynamic Black optimisation all help enhance your viewing experience while optimising energy usage.

#### Quantum Laser Engine

We incorporate laser phosphor illumination technology with blue laser diodes instead of traditional lamps to illuminate the Texas Instruments DLP digital micromirror device. The InFocus Quantum Laser engine produces vivid colours and exceptional image quality.

#### 4K Ultra HD Support on Native 1080p Models

Simply stunning image quality with up to 1920 x 1080 native resolution, HDMI 2.0 (HDCP 2.2) 4K Ultra HD and High dynamic range (HDR) support. The projected image has life texture details and improved image depth perception that pops off the screen.

### Image

Projection Technology	Texas Instruments DLP®
Panel Size	0.65"
Native Resolution	WXGA

Pixels	1280 x 800
Aspect Ratio	16:10
Contrast Ratio	2000000:1
Brightness (Lumens)	3500
Light Source	Quantum Laser
Light Source Life Maximum Hours	30000
Maximum Supported Resolution	1920 x 1080
Horizontal Sync. Range (KHz)	15 ~ 100
Vertical Sync. Range (Hz)	50 ~ 120
Uniformity (%)	85

## Optical

Lens	1.3x
Lens Zoom Adjustment	Manual
Optional Lenses	-
Image Offset (%)	112
Focal Length (mm)	16.901 ~ 21.607
F-Stop	2.43 ~ 2.78
Vertical Lens shift (%)	-
Horizontal Lens shift (%)	-
Keystone Adjustment	Automatic / Manual
Vertical Keystone Correction	±30°
Horizontal Keystone Correction	-
Projection Factor	1.19 ~ 1.54:1
Projection Distance (Meters/Feet)	1.2 ~ 7.7 / 3.9 ~ 25.3
Optical Zoom	Manual
Digital Zoom Demagnification / Magnification	0.8x ~ 2.0x
Focus Adjustment	Manual

## Connectivity

Analog Input	VGA, Composite Video
Analog Output	VGA
Digital Input	2x HDMI™ 1.4
Digital Output	-
Audio Input	3.5mm
Audio Output	3.5mm
Control	RS232, Micro USB
Service	Micro USB
Powered USB for Wireless Dongle	USB-A
3D Sync	-
Full 3D Support	Yes
3D Formats	All Major Formats Supported
Document Reader	-
Video Player	-
Photo Viewer	-
Music Player	-

PC Less Compatibility

-

## Power

Power Supply	100 ~ 240 V AC; 50 - 60 Hz
Power Consumption Max (W)	161
Power Consumption Min. (W)	138
Power Consumption Network Standby (W)	-
Power Consumption Standby (W)	<0.5

## General

Dimensions (W x H x D) (mm / in)	337 x 265 x 119.3 / 13.27 x 10.4 x 4.7
Product Weight (Kilograms/Pounds)	3,9 / 8,6
Lüftergeräusch (dB)	28 ~ 30
Audio (w)	1x 15
Betriebstemperatur (Celsius/Fahrenheit)	0 ~ 40 / 32 ~ 104
Betriebsfeuchtigkeit (%)	0 ~ 85
Max. Betriebshöhe (Meter / Fuß)	3048 / 10000
Lagertemperatur (Celsius/Fahrenheit)	-10 ~ 60 / 14 ~ 140
Lagerfeuchtigkeit (%)	0 ~ 85
Sicherheit	Kensington Lock Port™, PIN & Timer
In der Box	Projektor, IR-Fernbedienung (ohne Batterien), Netzkabel, VGA-Kabel, Projektor, Installationsanleitung, Objektivdeckel
Sicherheit und Vorschriften	CE, EAC, RoHS, cTUVus, CCC, FCC, FDA, NOM
Umwelt	WEEE, RoHS