

BE27ACSBK

Display

Panel Size (inch) : 27
Aspect Ratio : 16:09
Display Viewing Area (H x V) : 596.736 x 335.664 mm
Display Surface : Non-Glare
Backlight Type : LED
Panel Type : IPS
Viewing Angle (CR \geq 10, H/V) : 178°/ 178°
Pixel Pitch : 0.233mm
Resolution : 2560x1440
Color Space (sRGB) : 100%
Brightness (Typ.) : 350cd/m²
Contrast Ratio (Typ.) : 1200:01:00
ASUS Smart Contrast Ratio (ASCR) : 100000000:1
Display Colors : 16.7M
Response Time : 5ms(GTG)
Refresh Rate (Max) : Typ. 60Hz
Protection Glass : Nein
Flicker-free : Ja



Video Feature

Trace Free Technology : Ja
SPLENDID Technology : Yes
Color Temp. Selection : Yes(4 modes)
GamePlus : Nicht verfügbar
QuickFit : Yes
HDCP : Ja, 1.4
VRR Technology : Nicht verfügbar
Dark Boost : Ja
DisplayWidget : Nein
Low Blue Light : Yes
Web Camera : Yes(2.0M Pixels, Rotatable)

Audio Feature

Speaker : Ja (1,2Wx2)
Microphone : Yes(x2 for MIC-Array)

I/O Ports

USB-C x 1
DisplayPort 1.2 x 2 (Daisy Chain)
HDMI(v1.4) x 1
VGA Nicht verfügbar
USB Hub : 4x USB 3.2 Gen 1 Type-A
Earphone Jack : Ja
USB-C Power Delivery : 80W

Signal Frequency

Digital Signal Frequency : HDMI: 30~122 KHz (H) / 48~75 Hz (V)
DisplayPort, USB-C: 30~122 KHz (H) / 30~75 Hz (V)

Power Consumption

Power Consumption : < 21.3W
Power Saving Mode : < 0.5W
Power Off Mode : 0W (Hardwareschalter)
Voltage : 100-240V, 50/60Hz

Mechanical Design

Tilt : Yes (+35° ~ -5°)
Swivel : Yes (+180° ~ -180°)
Pivot : Ja (+90° ~ -90°)
Height Adjustment : 0~150mm
Lighting effect : Nicht verfügbar
VESA Wall Mounting : 100 x 100 mm
Kensington Lock : Ja

Dimensions (Esti.)

Phys. Dimension with Stand (W x H x D) : 612.4 x (441.8~547.8) x 259 mm
Phys. Dimension without Stand (W x H x D) : 612.4 x 427.3 x 56.1 mm
Box Dimension (W x H x D) : 713 x 502 x 228 mm

Weight (Esti.)

Net Weight with Stand : 8.6 Kg
Net Weight without Stand : 5.8 Kg
Gross Weight : 11.2 Kg

Accessories (vary by regions)

HDMI Kabel
Netzkabel
Ständer mit Schnellverschluss
Schnellstartanleitung
USB-C Kabel

Operation Temperature / Humidity

Operation temperature : 0~+40°C
Operation humidity : 10%~80%