



Artikel Nr.: 342031

Pendelleuchte, Filo Sat, Silber, 220-240V AC/50-60Hz, 60,00 W

Technische Daten

Charakteristik

Material	Metall
Farbe	Silber
Optik	
im Lieferumfang	



Elektrische Daten

Leistung	60,00 W
Eingangsspannung	220-240V AC/50-60Hz
Eingangsstrom	
Fassung / Sockel	E27
Anzahl Sockel	3
Netzgerät	
Anschlussmöglichkeit	Klemme
Schutzklasse I, II, III	I





Artikel Nr.: 342031

Pendelleuchte, Filo Sat, Silber, 220-240V AC/50-60Hz, 60,00 W

Lichtrichtung

Dreh- und Schwenkbereich	feststehend
Neigungswinkel	0°
Abstrahlverhalten	
Reflektor / Linse	symmetrisch

Abmessungen und Gewicht

Länge	
Breite	
Höhe	180 mm
Durchmesser	390 mm
Deckenabhängung	max. 1200 mm
Gewicht	

Rosettenmaß

Länge	
Breite	
Höhe	25 mm
Durchmesser	110 mm





Artikel Nr.: 342031

Pendelleuchte, Filo Sat, Silber, 220-240V AC/50-60Hz, 60,00 W

Grenzwerte

Betriebstemperatur	-5°C - +40°C
Lagertemperatur	
IP - Schutzart	IP 20

IP 20	Schutz gegen das Eindringen von Fremdkörper > 50 mm. Kein Schutz gegen das Eindringen von Wasser.
	Leuchte der Schutzklasse I bei der der Schutz gegen elektrischen Schlag nicht allein auf der Basisisolierung beruht, sondern die eine zusätzliche Sicherheitsvorkehrung derart enthält, dass berührbare leitfähige Teile mit Mitteln zum Anschluss an den Schutzleiter der festen Installation ausgerüstet sind, so dass im Fehlerfall der Basisisolierung berührbare leitfähige Teile nicht aktiv werden können.
	Aufgrund des komplexen Herstellungsprozesses von LED stellen die angegebenen Werte nur rein statistische Größen dar und müssen nicht zwingend den tatsächlichen Parametern jedes einzelnen LED-Moduls entsprechen, sondern können von den typischen Werten abweichen.



Article no.: 342031

Pendant lamp, Filo Sat, silver, 220-240V AC/50-60Hz, 60,00 W

Technical Data

General Characteristics

Material	metal
Colour	silver
Optics	
included in delivery	



Electrical Characteristics

Wattage	60,00 W
Input voltage	220-240V AC/50-60Hz
Input current	
Base (standard designation)	E27
Number of bases	3
Power supply unit	
Connection possibility	clamp
Protection class I, II, III	I





Article no.: 342031

Pendant lamp, Filo Sat, silver, 220-240V AC/50-60Hz, 60,00 W

Light Direction

Rotating and tilting range	fixed
Angle of inclination	0°
Radiation direction	
Reflector / lense	symmetrisch

Dimensions & Weight

Length	
Width	
Height	180 mm
Diameter	390 mm
Suspensions from ceiling	max. 1200 mm
Product Weight	

Rosette dimensions

Length	
Width	
Height	25 mm
Diameter	110 mm



Article no.: 342031

Pendant lamp, Filo Sat, silver, 220-240V AC/50-60Hz, 60,00 W

Absolute maximum ratings

Working temperature	-5°C - +40°C
Storage temperature	
IP - Code	IP 20

IP 20

Protection against penetration of foreign objects > 50 mm. No protection against penetration of water.



Lightings of Protection Class I in which the protection against electric shock is not based solely on isolation, but an additional safety measure contains such a way that accessible conductive parts are equipped with means for connection to the protective conductor of the fixed installation, so that in case of failure of the basic insulation exposed conductive parts cannot be active.



Because of the complex manufacturing process of the LED the above shown data are just a statistical size, which is not forced to be the realistic data of every LED.