




Wall Lights | 1xG9
6410



| Technische Daten | |
|---|----------------------|
| Sammlung | linealight |
| Installationsposition | Wand - Decke |
| Installation environment | Indoor |
| Lampenleistung | 1 x 33 W |
| Anschluss der Leuchte | 1 x G9 |
| Frequency | 50-60 Hz |
| Optic | Diffused |
| Light emission direction | frontal |
| Isolierklasse | 2 |
| IP | IP44 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammaren Oberflächen | Ja |
| CE | Ja |
| ETL | Nein |
| Notbeleuchtung | Nein |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein Kg |
| Einschließlich Kabel | Nein |
| Harzbeschichtung | Nein |
| Nettogewicht | 0.260 kg |
| Volumen | 0.004 m ³ |
| Packaging size | 180x125x195 mm |
| Number of packages | 1 |

Oberfläche Gehäuse

| | |
|-----------------|----------------|
| Material | Iron |
| Colour | chrome |
| Bearbeitungstyp | Electroplating |

Oberfläche Diffusor

| | |
|-----------------|----------------|
| Material | Glass |
| Colour | white |
| Bearbeitungstyp | Silk-screening |

Oberfläche Fassung

| | |
|----------|-------------|
| Material | PC |
| Colour | transparent |



Wall Lights | 1xG9
6410

Single emission wall lights for indoor application. Halogen lamp included 33W, lamp cap 1xG9.

The device body is made of iron and features a chrome finish, processed by means of electroplating; the diffuser is made of glass with a silk-screening treatment; the mounting frame is made of PC, with a transparent finish. The ingress protection degree is IP44; the total weight is of 0.260 kg.

The device features protection class II and can be wall lights or ceiling-mounted.

| Illuminotechnical Eigenschaften | |
|--|--------|
| Farbtemperatur | 2700 K |
| Farbwiedergabeindex | 100 Ra |
| Lichtstrom (Lichtquelle) | 460 lm |